

Applicant : David J. Alessio  
Appln. No. : 10/518,219  
Page : 2

In the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

1. (currently amended) A lighting device comprising:
  - a housing;
  - a first light emitting diode located on the housing;
  - a second light emitting diode located on the housing and spaced from the first light emitting diode;
  - a first magnifier lens arranged in a light path of the first light emitting diode for focusing a first light beam onto a target area;
  - a second magnifier lens arranged in a light path of the second light emitting diode for focusing a second light beam onto the target area such that the first light beam and the second light beam overlap on the target area;
  - a support member for supporting the first and second magnifier lenses relative to the first and second light emitting diodes, respectively; and
  - a rear housing coupled to a back side of the housing, the rear housing having a battery compartment.
2. (original) The lighting device as defined in claim 1, wherein the support member comprises a non-reflective inner wall.
3. (original) The lighting device as defined in claim 1, wherein the support member comprises a cover of the housing.
4. (original) The lighting device as defined in claim 3, wherein the cover comprises a substantially transparent material.

Applicant : David J. Alessio  
Appln. No. : 10/518,219  
Page : 3

5. (original) The lighting device as defined in claim 1, wherein the first and second magnifier lenses each comprise a convex magnifier lens.
6. (original) The lighting device as defined in claim 1, wherein the first and second magnifier lenses each comprise a plano convex magnifier lens.
7. (original) The lighting device as defined in claim 1, wherein the first and second magnifier lenses are arranged substantially orthogonal to the light path of the corresponding first and second light emitting diodes.
8. (original) The lighting device as defined in claim 1, wherein the device is employed on a flashlight.
9. (original) The lighting device as defined in claim 1 further comprising a circuit board fixed to the housing, wherein the first and second light emitting diodes are connected to the circuit board.
10. (currently amended) A lighting device comprising:
  - a housing;
  - a first light emitting diode located on the housing;
  - a second light emitting diode located on the housing and spaced from the first light emitting diode;
  - a first magnifier lens comprising a convex surface and arranged in a light path of the first light emitting diode for focusing a first light beam onto a target area;
  - a second magnifier lens comprising a convex surface and arranged in a light path of the second light emitting diode for focusing a second light beam onto the target area such that the first light beam and the second light beam overlap on the target area, wherein the second magnifier lens is spaced from the first magnifier lens;

Applicant : David J. Alessio  
Appln. No. : 10/518,219  
Page : 4

a cover disposed over a front of the housing, said cover supporting the first and second magnifier lenses relative to the first and second light emitting diodes, respectively; and

a rear housing coupled to a back side of the housing and the rear housing having a battery compartment.

11. (original) The lighting device as defined in claim 10, wherein the cover comprises a substantially transparent material.

12. (original) The lighting device as defined in claim 10, wherein the cover comprises a non-reflective inner wall.

13. (original) The lighting device as defined in claim 10, wherein the first and second magnifier lenses each comprise a convex magnifier lens.

14. (original) The lighting device as defined in claim 10, wherein the first and second magnifier lenses each comprise a plano convex magnifier lens.

15. (original) The lighting device as defined in claim 10, wherein the first and second magnifier lenses are arranged substantially orthogonal to the light path of the corresponding first and second light emitting diodes.

16. (original) The lighting device as defined in claim 10, wherein the device is employed on a flashlight.

17. ~~The lighting device as defined in claim 1, further comprising~~ A lighting device comprising:

a housing;

a first light emitting diode located on the housing;

Applicant : David J. Alessio  
Appln. No. : 10/518,219  
Page : 5

a second light emitting diode located on the housing and spaced from the first light emitting diode;

a first magnifier lens arranged in a light path of the first light emitting diode for focusing a first light beam onto a target area;

a second magnifier lens arranged in a light path of the second light emitting diode for focusing a second light beam onto the target area;

a support member for supporting the first and second magnifier lenses relative to the first and second light emitting diodes, respectively;

a rear housing coupled to a back side of the housing, the rear housing having a battery compartment; and

a headband strap.

18. (original) The lighting device as defined in claim 1, further comprising a third light emitting diode on the housing and a switch, the third light emitting diode providing a third light beam having a color varied from the first light beam and the second light beam, the switch having a first mode having the first light emitting diode, the second light emitting diode, and the third light emitting diode off, a second mode having the first light emitting diode and the second light emitting diode on, and a third mode having the third light emitting diode on.

19. (currently amended) A lighting device comprising:

a front housing having a front side and a back side;

a plurality of light emitting diodes located on the front housing, the plurality of light emitting diodes emitting light from the front side of the front housing;

a plurality of lenses arranged in front of the plurality of light emitting diodes; and

a rear housing coupled to a the back side of the front housing, the rear housing having a battery compartment.

Applicant : David J. Alessio  
Appln. No. : 10/518,219  
Page : 6

20. (currently amended) The lighting device as defined in claim 19, wherein the battery compartment comprises one or more batteries that supply power to the plurality of light emitting diodes.

21. (new) The lighting device as defined in claim 1, wherein the housing includes a front side and the back side, and the first light emitting diode and the second light emitting diode emit light from the front side of the housing.

22. (new) The lighting device as defined in claim 10, wherein the housing includes a front side and the back side, and the first light emitting diode and the second light emitting diode emit light from the front side of the housing.

23. (new) The lighting device as defined in claim 1, further including a headband strap.

24. (new) The lighting device as defined in claim 10, further including a headband strap.

25. (new) The lighting device as defined in claim 17, wherein the housing is pivotally connected to the rear housing to allow the housing and the light emitting diodes to be moved relative to the rear housing.

26. (new) The lighting device as defined in claim 10, wherein the housing is pivotally connected to the rear housing to allow the housing and the light emitting diodes to be moved relative to the rear housing.

27. (new) The lighting device as defined in claim 19, wherein the front housing is pivotally connected to the rear housing to allow the front housing and the light emitting diodes to be moved relative to the rear housing.